



# ESD Interlocking Floor Tiles - X Joint

## TECHNICAL DATASHEET

### DESCRIPTION

ESD Interlocking Floor Tiles are a tough, flexible and modern flooring solution. They can be used as your primary ground and are guaranteed to give ESD performance for the life of the tile.

These electrostatic dissipative, interlocking floor tiles are ideal for use in electronics and telecommunications factories, computer server rooms, production plants; such as pharmaceutical, paint, petrochemical and certain food production facilities where there may be a risk of dust explosion (sugar, floor dust etc).

### VARIATIONS

SKU	STYLE	COLOUR	SIZE** (mm)
084-0020	Floor Tile*	Grey	497 x 497
084-0021	Floor Pictotile	Yellow	497 x 497
084-0023	Ramp Edging	Yellow	497 x 90
084-0024	Ramp Corner Edging	Yellow	580 x 90
084-0022	UK Grounding Kit	Grey	497 x 497
084-0019	EU Grounding Kit	Grey	497 x 497

\*Sold per sqm (4 tiles per sqm)

\*\*+-0.3mm Tolerance



### FEATURES

- Chemically resistant
- Environmentally friendly
- Fire retardant
- Simple installation
- Smart modern appearance

### PROPERTIES

PROPERTY	RESULT
Thickness	6.8mm +/- 0.3mm
Weight	8.40kgs/m <sup>2</sup>
Guarantee	Lifetime manufacturer's guarantee
Anticipated service life	25 years +
Material	PVC
Joint	X joint

### GROUNDING KIT

Our ESD grounding kit is required for fitting floor tiles. The kit includes:

1. Earth bonding plug
2. Conductive grounding tape
3. Earth cord with 1 Megaohm resistor
4. ESD tile with grounding stud

1 kit required per 50m<sup>2</sup> of flooring

To request a quotation or for more information, please call **+44 (0)1473 836200**  
 email [info@antistat.co.uk](mailto:info@antistat.co.uk) or visit [www.antistat.co.uk](http://www.antistat.co.uk)

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2026 Antistat.

**TECHNICAL SPECIFICATIONS**

PROPERTIES	TEST STANDARDS	RESULT
Slip resistance	EN 14041:2004 DIN 51130:2004	Pass R10
Fire performance	BS 476: Part 7 DIN 13501: 2004	Class 1 spread of flame Bfl-S1 Does not support combustion
Stain resistance	EN 423	Good
Abrasion wear resistance	EN 13845 EN 649	Lifetime manufacturer's guarantee
Mechanical resistance	DIN 53516	17N/mm <sup>2</sup>
Resistance to hot objects/solder	-	Good
Thickness of wear layer	EN 429	6 to 10mm
Hardness	ISO 868	89-92 Shore A
Impact resistance	EN 13329-549	549kg/cm <sup>2</sup>
Noise reduction	EN 140-8	>46db
Determination of length, squareness and straightness:	BS EN 428:1993	<0.13% / 0.5mm maximum
Chemical resistance	EN 13529	Good resistance to most commonly used chemicals. Common acid oils and gas oil - no deterioration / not resistant to prolonged contact
Colour fastness	EN 50105-BO21	5

**PERFORMANCE & TEST RESULTS**

These ESD interlocking floor tiles have been independently tested against EN 14041:2018:

- Resistance ( $> 3.4 \times 10^4$  ohms and  $\leq 5.0 \times 10^6$  ohms)
- Prevents static generation ( $< 100$  volts)

The test results guarantee that this product complies with British Standard BS EN 61340-5-1:2016 and IEC 61340-5-1:2016

To request a quotation or for more information, please call **+44 (0)1473 836200**  
email [info@antistat.co.uk](mailto:info@antistat.co.uk) or visit [www.antistat.co.uk](http://www.antistat.co.uk)

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2026 Antistat.